


A1. Model No.:	A2. Product Name:
AMC-12L (Left Side) AMC-12R (Right Side)	12.3" HD Electronic Mirror Monitor System, Recording
<p>B1. Features:</p> <p>Monitor:</p> <ol style="list-style-type: none"> 2CH×1080P camera inputs IPS screen Automatic back lighting for automatic brightness control. Full-function remote control. DC: 10 - 32V. <p>Upper Camera:</p> <p>1080P WDR (wide dynamic range) Meet the angle requirements of Class II rearview mirror IP69K waterproof</p> <p>Lower Camera:</p> <p>1080P WDR (wide dynamic range) Meet the angle requirements of Class IV rearview mirror IP69K waterproof</p>	
<p>C1. Key Specifications:</p>	
<p>Monitor:</p> <p>LCD size: 12.3"</p> <p>Resolution: 1920×3(RGB)×720</p> <p>Maximum number of camera: 2 (Max. 720P/30fps)</p> <p>Audio input: no</p> <p>Max. brightness: 1000cd/m2</p> <p>Contrast: 1000:1</p> <p>Viewing angle monitor: U: 85° / D: 85°, R/L: 85° / 85°</p> <p>Split screen: yes</p> <p>Anti-vibration: 2.1G</p> <p>Power input: DC 10V-32V</p> <p>Operating temperature: -20~+70°C, RH90%</p> <p>Storage temperature: -30~+80°C, RH90%</p>	

Upper Camera		Lower Camera
Image Device:	1/2.8" CMOS	1/2.8" CMOS
Frame Rate:	30 fps	30 fps
Effective Pixels:	1920 (H) x 1080 (V)	1920 (H) x 1080 (V)
Pixel pitch	2.9 μm x 2.9 μm	2.9μm x 2.9 μm
Scanning System:	Progressive Scanning	Progressive Scanning
Sync. System:	Internal	Internal
Resolution:	1080P	1080P
Minimum Illumination:	0.1 Lux	0.1 Lux
Video Output:	1.0Vp-p, 75Ohm	1.0Vp-p, 75Ohm
Gamma Consumption:	0.45	0.45
AGC:	Auto	Auto
White Balance:	Auto	Auto
WDR	>100 dB	>100 dB
Electronic Shutter:	1/30(1/25)~1/50,000 Seconc	1/30(1/25)~1/50,000 Seconds
BLC:	Auto	Auto
Power Supply:	DC 12~32 V	DC 12~32 V
Connection:	4 PIN	4 PIN
Operating Temperature:	-40°C ~ 105°C, RH95%MAX	-40°C ~ 105°C, RH95%MAX.
Storage Temperature:	-50°C ~ 110°C, RH95%MAX	-50°C ~ 110°C, RH95%MAX.
Lens:	f = 6.0 mm	f = 2.3 mm
Lens Angle:	20°(H) 35°(V)	71°(H) 63°(V)